



- Cable Length Measurement
- Cable Fault Finder
- Tone Generator
- Cable Manager

For Professionals... Since 1857™

Now Available in Australia and New Zealand

MUMMETOOLS

Ranger Tor Kit

TIME DOMAIN REFLECTOMETRY SPREAD SPECTRUM



TDR-Spread Spectrum Technology

- Eliminates Interference when measuring cable
- Superior Accuracy up to ±(1% + 1 m)
- Broadens TDR operating environments
- Usable in Safety Extra Low Voltage (SELV) rated environments as defined by IEC*

Cable Length Measurement

- Up to 914 m
- Measure voice, data, video, doorbell, siamese, lamp-wire and NM cables

Cable Fault Finder

- Ensure compliance and identify cable runs outside specification
- Determine if cable run is broken or damaged

Tone Generator[†]

- Trace and identify cables
- Four tone cadences available

Cable Manager

- · Measure cable remaining in box or on reel
- Simplify cable estimating and bill jobs more accurately

Kit Includes:

- Ranger[™] TDR (VDV501-090)
- Adapter cord Set:
 - BNC to F-connector adapter
 - F-connector adapter
 - Insulated push-on F-connector to alligator clips
 - Insulated BNC connector to alligator clips
 - Insulated push-on F-connector to RJ45 modular plug
- Batteries 4 AA alkaline/LR6/15A
- · Custom designed polyester carrying case

*SELV is 60 volts DC or peak AC (45 volts RMS)

†Requires analogue tone probe – VDV526-054 or VDV500-060 (sold separately)

Features		Included		
Ranger™ TDR	VDV501-090	•		
Interface		Includes Multi-Adapter Set		
Measures Length	$ \longleftrightarrow $	•		
Length Measurement Method	(TDR-SS) Spread Spectrum Time Domain Reflectometry	•		
Accuracy and Measurement Resolution:	± (1% + 1 m)	•		
Maximum Cable Length Measurement	914 m	•		
Common Cable Length Ranges	Coaxial Cable: Data Cable: Electrical Cable:	0 - 609 m 0 - 457 m 0 - 305 m		
Imperial & Metric Results	ft/m	•		
On-Board Calibration Memory	MEM	2 Storage Locations		
Open Fault	>>< <u>X-</u>	•		
Short Fault	\sim	•		
Display		57 mm Backlit LCD		
Multiple Style Tone Generator†	11	•		
Voltage Warning	A	•		
Auto Power Off	Apo	•		
Low Battery		•		



VDV501-815

Cat. No.	Batteries	Battery Life	Height	Width	Depth	Weight
VDV501-815	4 AA alkaline batteries included	standby: 4 hours active: 15 hours (average)	173 mm	80 mm	33 mm	340 g with batteries

AWARNING: Read, understand, and follow all instructions, cautions and warnings attached to and/or packed with all test and measurement devices before each use.



P.O. Box 126, Lonsdale SA 5160 T: +61 8 8186 0000 F: +61 8 8186 2222 www.kleintools.com.au



Find us here



