

KLEIN TOOLS®

DIGITAL MULTIMETERS



FEATURES	ET600
Drop Protection	3.3ft (1m)
Safety Rating	CAT IV 600V CAT III 1000V
Test Voltages	125V, 250V, 500V, 1000V
AC Voltage	1000V
DC Voltage	1000V
Insulation Resistance	4000MΩ
Resistance	400kΩ
Test Lock	●
Live Circuit Detection	●
True RMS	●
Audible Continuity	●
Backlight	●
Auto Ranging	●
Auto Zero	●
Data Hold	●
Max/Min Value	●
Auto Power-Off	●
LCD Display Count	4000
Bar Graph	●
Over-Range Indication	●
Case Included	●
Smart Mode	—

Slim Profile



FEATURES	MM325	MM420	MM450	MM460S	MM720
Drop Protection	6.5ft (2m)	6.5ft (2m)	6.5ft (2m)	6.5ft (2m)	6.5ft (2m)
Ingress Protection	—	—	—	—	IP42
Safety Rating	CAT III 600V	CAT III 600V	CAT III 600V	CAT III 600V	CAT IV 600V CAT III 1000V
AC Voltage	600V	600V	600V	600V	1000V
DC Voltage	600V	600V	600V	600V	1000V
AC Current	—	10A	10A	10A	10A
DC Current	10A	10A	10A	10A	10A
Resistance	2MΩ	50MΩ	50MΩ	50MΩ	60MΩ
DC Millivolts	●	●	●	●	●
AC Milliamps	—	●	●	●	●
DC Milliamps	●	●	●	●	●
AC Microamps	—	●	●	●	●
DC Microamps	●	●	●	●	●
True RMS	●	●	●	●	●
Audible Continuity	●	●	●	●	●
Backlight	●	●	Backlit Hi-Vis Reverse Contrast (FFSTN)	Backlit Hi-Vis Reverse Contrast (FFSTN)	Backlit Hi-Vis Reverse Contrast (FFSTN)
Temperature	—	-40° - 1832°F (-40° - 1000°C)	-40° - 1832°F (-40° - 1000°C)	-40° - 1832°F (-40° - 1000°C)	-40° - 1832°F (-40° - 1000°C)
Low Impedance	—	—	—	—	●
Auto Ranging	—	●	●	●	●
Range Hold	—	●	●	●	●
Data Hold	●	●	●	●	●
Diode Test	●	●	●	●	●
Capacitance Test	—	400μF	400μF	4000μF	6000μF
Frequency / Duty Cycle	—	10Hz-50kHz 1.0% to 99.9% (≤10kHz)	10Hz-50kHz 1.0% to 99.9% (≤10kHz)	10Hz-50kHz 1.0% to 99.9% (≤10kHz)	10Hz-50kHz 1.0% to 99.9% (≤10kHz)
Max / Min	—	●	●	●	●
Lead Alert Warning	●	●	●	●	—
Magnetic Mount	Available As Accessory	Available As Accessory	Available As Accessory	Available as Accessory	Available As Accessory
Auto Power-Off	●	●	●	●	●
Battery Test	●	—	—	—	—
LCD Display Count	2000	4000	4000	4000	6000
Kickstand	●	●	—	●	●
Case Included	—	—	●	●	●
Smart Mode	—	—	—	●	—